



HAISHA Paints

Ceiling Emulsion,

is a revolutionary super white emulsion made specially for ceilings, which hides all undulations and makes your home look bright and fresh always.

BENEFITS



High Brightness Formulated with special pigments and co-polymer emulsion binder, which lend a super white matt finish to the ceiling, making the room look brighter.



No Spattering Made with a highly efficient binder that prevents paint splattering (when applied with roller), for faster, comfortable application.

PRODUCT FEATURES

WHITENESS	COLOURS AVAILABLE	FINISH	DRY TO TOUCH
HIGH	WHITE	MATT	10-15 min

PACKS



Shelf life: 3 years from date of manufacture in original tightly closed containers away from direct sunlight and excessive heat.

COVERAGE

100-110 Sq. Ft./Ltr in 2 coats*
on smooth masonry surface by brush/roller.

AREAS OF APPLICATION

Interior ceiling, false ceiling of POP, asbestos sheet.

-HOW TO APPLY-

A) Pre-Painting Steps

- New plaster surfaces should be allowed to mature for a minimum period of 2 months. Surface should be sanded to remove loose material.
- Earlier coating of lime-wash should be scraped off; other coatings, if in sound condition, need not be removed and can be sanded to roughen the surface.
- Surface imperfection/dents may be filled with suitable Dr. Fixit Waterproof Wall putty.
- Waterproof the areas that have dampness using Dr. Fixit waterproofing solutions.
- Fill cracks using Dr. Fixit Crack Filler.

B) Application Process

APPLICATION	THINNER	DILUTION %	APPLICATION VISCOSITY*	RECOATING PERIOD*
Sand the surface with Sandpaper 180 and wipe clean.				
HAISHA Paints Interior Wall Primer (Brush/Roller)	Water	1:1	Brush 15-20	3-4 Hours
Dr. Fixit Waterproof Wall Putty	Water	35-45% (mixing ratio)	NA	4-6 Hours
Sand surface with Sandpaper 320 and wipe clean				
HAISHA Paints Interior Wall Primer (Brush/Roller)	Water	1:1	Brush 15-20	3-4 Hours
Gentle sanding to remove dust, if any, with Sandpaper 320 and wipe clean				
HAISHA Paints Ceiling Emulsion 1 st Coat (Brush/Roller)	Water	50-60% 20-30%	Brush/Roller 70-80/60-70	3-4 Hours
HAISHA Paints Ceiling Emulsion 2 nd Coat (Brush/Roller)	Water	50-60% 20-30%	Brush/Roller 70-80/60-70	3-4 Hrs

*Viscosity is measured through a Ford Cup.

*Recoating period is quoted for 30°C and 50% relative humidity; these may vary under different conditions.



ADDITIONAL INFO

Post painting care

- To remove any dirt/dust, clean the painted surface after 30 days with mild soap solution.
- Do not use harsh, abrasive cleaners.
- In case of algae or fungus, clean the surface using Bio Wash solution.

Precautions

- Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hours of application.
- Do not over-thin or overextend the brush.
- Stir thoroughly before use.



SAFETY FEATURES

Kindly refer to the MSDS for HAISHA Paints Ceiling Emulsion which gives detailed information on safety measures while handling the paint, which is available on request.

Store the container with lid in an upright position, in a cool, dry place.

Keep out of reach of children and away from eatables.

Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of skin contact wash the skin with soap and plenty of water. Get medical attention if irritation develops or persists.

Do not breathe vapor or spray. It is recommended to wear a suitable nose mask during sanding and surface preparation to avoid dust inhalation.

Do not pour leftover paint down the drain or in water courses.

No added lead, mercury, or chromium compound.

TECHNICAL DETAILS

1

DRYING TIME (@ 30°C / 50-60% R.H.)

Surface dry (10-15 mins)
Re-coating period (3-4 hrs.)

2

SHEEN LEVELS

2-3 at 60° GH

3

FLASH POINT IS101/1987 PART 1 SEC 6

NA

4

SUPPLY VISCOSITY (KREB UNIT @ 30°C)

102-120 KU

5

WEIGHT PER LITRE

1.38 -1.43 Kg/Ltr
(1:1 Dilution method)

6

STABILITY OF THINNED PAINTS

To be used within
24 hours

7

SHELF LIFE

36 months from the date of mfg. when stored in the sealed original container.

Emerging India Division, ramkrishna mandir road, post box no. 17411, andheri (e) mumbai 400059 india
Tel 18002666066 • fax +91-22-2835 7008 • website : www.haishapaints.com • e-mail : csc@pidilite.com • toll free no. 1800 22 5502

DISCLAIMER : WHILE THE COMPANY GUARANTEES ITS PRODUCTS AGAINST DEFECTIVE MATERIALS, THE USE AND APPLICATION OF THESE PRODUCTS ARE MADE WITHOUT GUARANTEE SINCE THE CONDITIONS OF THEIR APPLICATION ARE BEYOND ITS CONTROL. IT IS RECOMMENDED TO VERIFY WITH THE COMPANY THAT THE PRODUCT IS SUITABLE FOR THE INTENDED USE, AND THAT THIS DATA SHEET VERSION IS THE LATEST ONE. THE COMPANY MAY MODIFY IT WITHOUT PRIOR NOTICE. TECHNICAL CHARACTERISTICS ARE LISTED FOR GUIDANCE ONLY. FOR MORE INFORMATION, PLEASE CONTACT THE COMPANY OFFICE IN YOUR LOCATION.