



HAISHA Paints Classic Interior Emulsion is an economical acrylic emulsion paint that gives a uniform finish to the wall. It is a value-for-money emulsion for customers using distempers or similar wall finishes.

BENEFITS



High binding formulation Helps create a smooth and cohesive paint film on the walls.



High Coverage Gives plastic paint-like finish at the same per sq. ft. cost as that of distemper.



Easy-to-apply Slow drying nature facilitates comfortable application with brush/roller, thereby giving uniform finish, unlike other emulsions.

PRODUCT FEATURES

SURFACE	COLOURS	FINISH	DRY TO TOUCH
INTERIOR	700+SHADES	MATT	25-30 min

PACKS



Shelf life: 3 years from date of manufacture in original tightly closed containers away from direct sunlight and excessive heat.

COVERAGE

90-100 Sq.ft./litre for 2 coats*
on smooth masonry surface by brush/roller.

AREAS OF APPLICATION

Interior ceiling, walls of cement plaster, asbestos sheets, gypsum boards, etc.

-HOW TO APPLY-

A) Pre-Painting Steps

- New plaster surfaces should be allowed to mature for a minimum period of 2 months. Surface should be sanded to remove loose material.
- Earlier coating of lime-wash should be scraped off; other coatings, if in sound condition, need not be removed and can be sanded to roughen the surface.
- Surface imperfection/dents may be filled with suitable Dr. Fixit Waterproof Wall putty..
- Waterproof the areas that have dampness using Dr. Fixit waterproofing solutions.
- Fill cracks using Dr. Fixit Crack Filler.

B) Application Process

APPLICATION	THINNER	DILUTION %	APPLICATION VISCOSITY*	RECOATING PERIOD*
SANDING Sand the surface with Sandpaper 180 and wipe clean				
HAISHA Paints Interior Wall Primer (Brush/Roller)	Water	100%	Brush 15-20	3-4 Hours
Dr. Fixit Waterproof Wall Putty	Water	35-45% (Mixing Ratio)	NA	4-6 Hours
SANDING Sand the surface with Sandpaper 320 and wipe clean				
HAISHA Paints Interior Wall Primer (Brush/Roller)	Water	100%	Brush 15-20	3-4 Hours
SANDING Gentle sanding to remove the dust if any with Sandpaper 320 and wipe clean				
HAISHA Paints Classic Interior Emulsion 1 st Coat (Brush/Roller)	Water	35-40%	Brush/Roller 60-70 sec	3-4 Hours
HAISHA Paints Classic Interior Emulsion 2 nd Coat (Brush/Roller)	Water	35-40%	Brush/Roller 60-70 sec	3-4 Hrs

*Viscosity is measured through a Ford Cup.

*Recoating period is quoted for 30°C and 50% Relative Humidity, these may vary under different conditions.



HOW TO CHOOSE COLORS

HAISHA Paints Fan-deck

Interior Books of Colours*

Shade card*

These shades are for reference only. Please refer to the HAISHA Paints Fandek for correct shade reference.

ADDITIONAL INFO

Post painting care

- For best performance of the paint, ensure proper washing and cleaning of all algal and fungal growth at regular interval of 6 months.

Precautions

- Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hours of application.
- Do not over-thin or overextend the brush.
- Stir thoroughly before use.

TECHNICAL DETAILS

1

DRYING TIME (@ 30°C / 50-60% R.H.)

**Surface dry (25-30 minutes)
Re-coating period (3-4 hours.)**

2

FINISH TO TOUCH

Smooth and uniform

3

FLASH POINT IS101/1987 PART 1 SEC 6

NA

4

SUPPLY VISCOSITY (KREB UNIT @ 30°C)

90- 100 KU

5

WEIGHT PER LITRE

**1.18 -1.24 Kg/lit
(1:1 Dilution method)**

6

STABILITY OF THINNED PAINTS

**To be used within
24 hours**

7

SHELF LIFE

**36 months from the date of mfg. when stored in the sealed
original container**



SAFETY FEATURES

Kindly refer to the MSDS for HAISHA Paints Classic Interior Emulsion which gives detailed information on safety measures while handling the paint, which is available on request.

Store the container with lid in an upright position, in a cool, dry place.

Keep out of reach of children and away from eatables.

Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of skin contact wash the skin with soap and plenty of water. Get medical attention if irritation develops or persists.

Do not breathe vapor or spray. It is recommended to wear a suitable nose mask during sanding and surface preparation to avoid dust inhalation.

Do not pour leftover paint down the drain or in water courses.

No added lead, mercury, or chromium compound

Emerging India Division, ramkrishna mandir road, post box no. 17411, andheri (e) mumbai 400059 india
Tel 18002666066 • fax +91-22-2835 7008 • website : www.haishapaints.com • e-mail : csc@pidilite.com • toll free no. 1800 22 5502

DISCLAIMER : WHILE THE COMPANY GUARANTEES ITS PRODUCTS AGAINST DEFECTIVE MATERIALS, THE USE AND APPLICATION OF THESE PRODUCTS ARE MADE WITHOUT GUARANTEE SINCE THE CONDITIONS OF THEIR APPLICATION ARE BEYOND ITS CONTROL. IT IS RECOMMENDED TO VERIFY WITH THE COMPANY THAT THE PRODUCT IS SUITABLE FOR THE INTENDED USE, AND THAT THIS DATA SHEET VERSION IS THE LATEST ONE. THE COMPANY MAY MODIFY IT WITHOUT PRIOR NOTICE. TECHNICAL CHARACTERISTICS ARE LISTED FOR GUIDANCE ONLY. FOR MORE INFORMATION, PLEASE CONTACT THE COMPANY OFFICE IN YOUR LOCATION.