



HAISHA Paints
Interior Wall Primer
is a water-thinnable
primer suitable for
application on interior
walls.

BENEFITS



Superior Whiteness Formulated with special pigments which lend superior whiteness, allowing for excellent hiding.



Easy to apply Allows brush or rollers to spread easily, leading to a delightful painting experience.



Slow Drying Allows time for covering large walls without leaving behind any brush/separation marks.

PRODUCT FEATURES

APPLICATION SURFACE

INTERIORS

COLOURS

WHITE

DRY TO TOUCH

15 minutes

PACKS



Shelf life: 3 years from date of manufacture in original tightly closed containers away from direct sunlight and excessive heat.

COVERAGE

220-225 Sq.ft./Litre for 1 coat*
on smooth masonry surface by brushing.

AREAS OF APPLICATION

Interior ceiling, walls of cement plaster, asbestos sheets, gypsum boards, etc.

-HOW TO APPLY-

A) Pre-Painting Steps

- New plaster surfaces should be allowed to mature for a minimum period of 2 months. Surface should be sanded to remove loose material.
- Earlier coating of lime-wash should be scraped off; other coatings, if in sound condition, need not be removed and can be sanded to roughen the surface.
- Surface imperfection/dents may be filled with suitable Dr. Fixit Waterproof Wall putty.
- Waterproof the areas that have dampness using Dr. Fixit waterproofing solutions.
- Fill cracks using Dr. Fixit Crack Filler.

B) Application Process

APPLICATION	THINNER	DILUTION %	APPLICATION VISCOSITY*	RECOATING PERIOD*
SANDING Sand the surface with Sandpaper 180 and wipe clean				
HAISHA Paints Interior Wall Primer (Brush/Roller)	Water	100%	Brush 15-20	3-4 Hours
Dr. Fixit Waterproof Wall Putty	Water	35-45% (mixing ratio)	NA	4-6 Hours
SANDING Sand the surface with Sandpaper 180 and wipe clean				
HAISHA Paints Interior Wall Primer (Brush/Roller)	Water	100%	Brush 15-20	3-4 Hours

*Viscosity is measured through a Ford Cup.

*Recoating period is quoted for 30°C and 50% Relative Humidity, these may vary under different conditions.



ADDITIONAL INFO

Post painting care

- For best performance of the paint, ensure proper washing and cleaning of all algal and fungal growth at regular interval of 6 months.

Precautions

- Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hours of application.
- Do not over-thin or overextend the brush.
- Stir thoroughly before use.



SAFETY FEATURES

Kindly refer to the MSDS for HAISHA Paints Interior wall primer which gives detailed information on safety measures while handling the paint, which is available on request.

Store the container with lid in an upright position, in a cool, dry place.

Keep out of reach of children and away from eatables.

Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of skin contact wash the skin with soap and plenty of water. Get medical attention if irritation develops or persists.

Do not breathe vapor or spray. It is recommended to wear suitable nose mask during sanding and surface preparation to avoid dust inhalation.

Do not pour leftover paint down the drain or in water courses.

No added lead, mercury, or chromium compound

TECHNICAL DETAILS

1 DRYING TIME (@ 30°C / 50-60% R.H.) Surface dry (10 – 15 minutes) Re-coating period (3-4 hrs.)	2 FINISH TO TOUCH Smooth and uniform
3 FLASH POINT IS101/1987 PART 1 SEC 6 NA	4 SUPPLY VISCOSITY (KREB UNIT @ 30°C) 90-100 KU
5 WEIGHT PER LITRE 1.35 -1.43Kg/lit (1:1 Dilution method)	6 SHELF LIFE 36 months from the date of Mfg. when stored in the sealed original container

Emerging India Division, ramkrishna mandir road, post box no. 17411, andheri (e) mumbai 400059 india
 Tel 18002666066 • fax +91-22-2835 7008 • website : www.haishapaints.com • e-mail : csc@pidilite.com • toll free no. 1800 22 5502

DISCLAIMER : WHILE THE COMPANY GUARANTEES ITS PRODUCTS AGAINST DEFECTIVE MATERIALS, THE USE AND APPLICATION OF THESE PRODUCTS ARE MADE WITHOUT GUARANTEE SINCE THE CONDITIONS OF THEIR APPLICATION ARE BEYOND ITS CONTROL. IT IS RECOMMENDED TO VERIFY WITH THE COMPANY THAT THE PRODUCT IS SUITABLE FOR THE INTENDED USE, AND THAT THIS DATA SHEET VERSION IS THE LATEST ONE. THE COMPANY MAY MODIFY IT WITHOUT PRIOR NOTICE. TECHNICAL CHARACTERISTICS ARE LISTED FOR GUIDANCE ONLY. FOR MORE INFORMATION, PLEASE CONTACT THE COMPANY OFFICE IN YOUR LOCATION.