



HAISHA Paints Luxury Interior Emulsion- High Sheen is a water-based, pure acrylic interior wall finish. Thanks to its Pearl X technology, the special extender pigments create a multi-layer high sheen paint film on walls, which does not allow stains to penetrate and maintains the shine despite multiple washes.

BENEFITS



Stain Resistance Superior technology resists common household stains like coffee, mud, pickle, etc., and enables paint film to be cleaned easily, keeping walls fresh and bright.



High Sheen High sheen paint film offers a rich premium look to walls.



Superior Hiding Unmatched opacity on any shade, thereby saving time and cost.

PRODUCT FEATURES

WASHABILITY	COLOURS	FINISH	DRY TO TOUCH
HIGH	WHITE + 1200 SHADES	SHEEN	20-25 min

PACKS



Shelf life: 3 years from date of manufacture in original tightly closed containers away from direct sunlight and excessive heat.

COVERAGE

120-130 Sq. Ft./Ltr in 2 coats*
on smooth masonry surface by brush/roller.

AREAS OF APPLICATION

Interior ceiling, walls of cement plaster, asbestos sheets, gypsum boards, etc.

-HOW TO APPLY-

A) Pre-Painting Steps

- New plaster surfaces should be allowed to mature for a minimum period of 2 months. Surface should be sanded to remove loose material.
- Earlier coating of lime-wash should be scraped off; other coatings, if in sound condition, need not be removed and can be sanded to roughen the surface.
- Surface imperfection/dents may be filled with suitable Dr. Fixit Waterproof Wall putty.
- Waterproof the areas that have dampness using Dr. Fixit waterproofing solutions.
- Fill cracks using Dr. Fixit Crack Filler.

B) Application Process

APPLICATION	THINNER	DILUTION %	APPLICATION VISCOSITY*	RECOATING PERIOD*
SANDING Sand the surface with Sandpaper 180 and wipe clean				
HAISHA Paints Interior Wall Primer (Brush/Roller)	Water	100%	Brush 15-20	3-4 Hours
Dr. Fixit WP Wall putty	Water	35-45% (mixing ratio)	NA	4-6 Hours
SANDING Sand the surface with Sandpaper 320 and wipe clean				
HAISHA Paints Interior Wall Primer (Brush/Roller)	Water	100%	Brush 15-20	3-4 Hours
SANDING Gentle sanding to remove dust, if any, with Sandpaper 320 and wipe clean				
HAISHA Paints Luxury Interior Emulsion 1 st Coat (Brush/Roller)	Water	40-50%	Brush/Roller 60-70	3-4 Hours
HAISHA Paints Luxury Interior Emulsion 2 nd Coat (Brush/Roller)	Water	40-50%	Brush/Roller 60-70	3-4 Hrs

*Viscosity is measured through a Ford Cup.

*Recoating period is quoted for 30°C and 50% Relative Humidity, these may vary under different conditions.



HOW TO CHOOSE COLORS

HAISHA Paints Fan-deck

Interior Books of Colours*

Shade card*

*These shades are for reference only. Please refer to the HAISHA Paints Fandek for correct shade reference.

ADDITIONAL INFO

Post painting care

- For the best performance of the paint, ensure proper washing and cleaning of algal and fungal growth at regular intervals of 6 months.
- For removing household stains like pencil, tea, coffee, crayon etc., use 5% mild soap solution. Use a sponge/clean cloth to remove the stains.
- In case of tough stains like turmeric, pickle, oil, etc., use a mild detergent solution for cleaning the stains.
- The best way to remove stains completely is to remove them immediately

Precautions

- Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hours of application.
- Do not over-thin or overextend the brush.
- Stir thoroughly before use.

TECHNICAL DETAILS

1

DRYING TIME (@ 30°C / 50-60% R.H.)

Surface dry (20-25 mins)
Re-coating period (3-4 hrs.)

2

SHEEN LEVELS

13-14 at 60 deg GH

3

FLASH POINT IS101/1987 PART 1 SEC 6

NA

4

SUPPLY VISCOSITY (KREB UNIT @ 30°C)

110-115 KU

5

WEIGHT PER LITRE

1.23 -1.28 Kg/lit
(1:1 Dilution method)

6

STABILITY OF THINNED PAINTS

To be used within
24 hours

7

SHELF LIFE

36 months from the date of Mfg. when stored in the sealed original container



SAFETY FEATURES

Kindly refer to the MSDS for HAISHA Paints Luxury Interior Emulsion which gives detailed information on safety measures while handling the paint, which is available on request.

Store the container with lid in an upright position, in a cool, dry place.

Keep out of reach of children and away from eatables.

Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of skin contact, wash the skin with soap and plenty of water. Get medical attention if irritation develops or persists.

Do not breathe vapor or spray. It is recommended to wear a suitable nose mask during sanding and surface preparation to avoid dust inhalation.

Do not pour leftover paint down the drain or in water courses.

No added lead, mercury, or chromium compound.

Emerging India Division, ramkrishna mandir road, post box no. 17411, andheri (e) mumbai 400059 india
Tel 18002666066 • fax +91-22-2835 7008 • website : www.haishapaints.com • e-mail : csc@pidilite.com • toll free no. 1800 22 5502

DISCLAIMER : WHILE THE COMPANY GUARANTEES ITS PRODUCTS AGAINST DEFECTIVE MATERIALS, THE USE AND APPLICATION OF THESE PRODUCTS ARE MADE WITHOUT GUARANTEE SINCE THE CONDITIONS OF THEIR APPLICATION ARE BEYOND ITS CONTROL. IT IS RECOMMENDED TO VERIFY WITH THE COMPANY THAT THE PRODUCT IS SUITABLE FOR THE INTENDED USE, AND THAT THIS DATA SHEET VERSION IS THE LATEST ONE. THE COMPANY MAY MODIFY IT WITHOUT PRIOR NOTICE. TECHNICAL CHARACTERISTICS ARE LISTED FOR GUIDANCE ONLY. FOR MORE INFORMATION, PLEASE CONTACT THE COMPANY OFFICE IN YOUR LOCATION.