



## HAISHA Paints

### Select Interior

**Emulsion** is a washable emulsion, which lets you easily clean stains and dirt on walls, offering a smooth finish.

#### BENEFITS



**Higher Coverage & Opacity** It is formulated from highly efficient co-polymer emulsion binders and special pigments to give higher coverage & hiding..



**High Washability:** Smooth emulsion finish has high washability than regular emulsion in the market.

#### PRODUCT FEATURES

| WASHABILITY | COLOURS             | FINISH      | DRY TO TOUCH     |
|-------------|---------------------|-------------|------------------|
| <b>HIGH</b> | <b>1100+ SHADES</b> | <b>MATT</b> | <b>25-30 min</b> |

#### PACKS



Shelf life: 3 years from date of manufacture in original tightly closed containers away from direct sunlight and excessive heat.

#### COVERAGE

**110-120 Sq.ft./Ltr in 2 coats\***  
on smooth masonry surface by  
brushing/roller.

#### AREAS OF APPLICATION

**Interior ceiling, walls of cement  
plaster, asbestos sheets,  
gypsum boards, etc.**

## -HOW TO APPLY-

### A) Pre-Painting Steps

- New plaster surfaces should be allowed to mature for a minimum period of 2 months. Surface should be sanded to remove loose material.
- Earlier coating of lime-wash should be scraped off; other coatings, if in sound condition, need not be removed and can be sanded to roughen the surface.
- Surface imperfection/dents may be filled with Dr. Fixit Waterproof wall putty.
- Waterproof the areas that have dampness using Dr. Fixit waterproofing solutions.
- Fill cracks using Dr. Fixit Crack Filler.

### B) Application Process

| APPLICATION                                                                | PRODUCT CODE | THINNER               | DILUTION %           | APPLICATION VISCOSITY* | RECOATING PERIOD* |
|----------------------------------------------------------------------------|--------------|-----------------------|----------------------|------------------------|-------------------|
| SANDING Sand the surface with Sandpaper 180 and wipe clean                 |              |                       |                      |                        |                   |
| HAISHA Paints Interior Wall Primer (Brush/Roller)                          |              | Water                 | 100%                 | Brush 15-20            | 3-4 Hours         |
| Dr. Fixit WP Wall putty                                                    | Water        | 35-45% (Mixing ratio) | Based on requirement | Supply consistency     | 4-6 Hours         |
| SANDING Sand the surface with Sandpaper 180 and wipe clean                 |              |                       |                      |                        |                   |
| HAISHA Paints Interior Wall Primer (Brush/Roller)                          |              | Water                 | 100%                 | Brush/Roller 60-70 sec | 3-4 Hours         |
| SANDING Sand the surface with Sandpaper 320 and wipe clean                 |              |                       |                      |                        |                   |
| HAISHA Paints Select Interior Emulsion 1 <sup>st</sup> Coat (Brush/Roller) |              | Water                 | 50-60% 40-50%        | Brush/Roller 60-70 sec | 3-4 Hours         |
| HAISHA Paints Select Interior Emulsion 2 <sup>nd</sup> Coat (brush/roller) |              | Water                 | 50-60% 40-50%        | Brush/Roller 60-70 sec | 3-4 Hrs           |

\*Viscosity is measured through a Ford Cup.

\*Recoating period is quoted for 30°C and 50% Relative Humidity, these may vary under different conditions.



## HOW TO CHOOSE COLORS



HAISHA Paints Fan-deck

Interior Books of Colours\*

Shade card\*

*\*These shades are for reference only. Please refer to the HAISHA Paints Fandec for correct shade reference.*

## ADDITIONAL INFO

### Post painting care

- For best performance of the paint, ensure proper washing and cleaning of all algal and fungal growth at regular interval of 6 months.

### Precautions

- Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hours of application.
- Do not over-thin or overextend the brush.
- Stir thoroughly before use.

## TECHNICAL DETAILS

1

DRYING TIME (@ 30°C / 50-60% R.H.)

**Surface dry (10-15 mins)  
Re-coating period (3-4 hrs.)**

2

SHEEN LEVELS

**2-4 at 60 deg GH**

3

FLASH POINT IS101/1987 PART 1 SEC 6

**NA**

4

SUPPLY VISCOSITY (KREB UNIT @ 30°C)

**90- 105 KU**

5

WEIGHT PER LITRE

**1.40 -1.45 Kg/lit  
(1:1 Dilution method)**

6

STABILITY OF THINNED PAINTS

**To be used within  
24 hours**

7

SHELF LIFE

**36 months from the date of Mfg. when stored in the sealed  
original container**



## SAFETY FEATURES

Kindly refer to the MSDS for HAISHA Paints Select Interior Emulsion which gives detailed information on safety measures while handling the paint, which is available on request.

Store the container with lid in an upright position, in a cool, dry place.

Keep out of reach of children and away from eatables.

Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of skin contact wash the skin with soap and plenty of water. Get medical attention if irritation develops or persists.

Do not breathe vapor or spray. It is recommended to wear suitable nose mask during sanding and surface preparation to avoid dust inhalation.

Do not pour leftover paint down the drain or in water courses.

No added lead, mercury, or chromium compound

Emerging India Division, ramkrishna mandir road, post box no. 17411, andheri (e) mumbai 400059 india  
Tel 18002666066 • fax +91-22-2835 7008 • website : [www.haishapaints.com](http://www.haishapaints.com) • e-mail : [csc@pidilite.com](mailto:csc@pidilite.com) • toll free no. 1800 22 5502

DISCLAIMER : WHILE THE COMPANY GUARANTEES ITS PRODUCTS AGAINST DEFECTIVE MATERIALS, THE USE AND APPLICATION OF THESE PRODUCTS ARE MADE WITHOUT GUARANTEE SINCE THE CONDITIONS OF THEIR APPLICATION ARE BEYOND ITS CONTROL. IT IS RECOMMENDED TO VERIFY WITH THE COMPANY THAT THE PRODUCT IS SUITABLE FOR THE INTENDED USE, AND THAT THIS DATA SHEET VERSION IS THE LATEST ONE. THE COMPANY MAY MODIFY IT WITHOUT PRIOR NOTICE. TECHNICAL CHARACTERISTICS ARE LISTED FOR GUIDANCE ONLY. FOR MORE INFORMATION, PLEASE CONTACT THE COMPANY OFFICE IN YOUR LOCATION.